



**Broadband Solutions**  
**SV4G**  
**Four-way Splitter, 5–1002 MHz**



## Environmental Specifications

Operating Temperature	-40 °C to +60 °C (-40 °F to +140 °F)
Safety Standard	CE   EN 60728-4   SCTE

## Electrical Specifications Isolation

Isolation at Frequency Band, tap to output, typical	35.0 dB @ 5–15 MHz   40.0 dB @ 15–45 MHz   35.0 dB @ 50–300 MHz   30.0 dB @ 300–1002 MHz
---	--

## Electrical Specifications

Power Passing	No
Impedance	75 ohm
Operating Frequency Band	5 – 1002 MHz
Insertion Loss at Frequency Band, typical	7.0 dB @ 5–550 MHz   8.0 dB @ 550–1002 MHz
Frequency Response	±0.3 dB
Return Loss at Frequency Band, input, typical	25 dB @ 5–45 MHz   22 dB @ 50–1002 MHz
Return Loss at Frequency Band, output, typical	25 dB @ 5–45 MHz   22 dB @ 50–1002 MHz
Spurious Signals/2nd Order Harmonics, before surge	<-60 dBmV
Shielding Effectiveness, minimum	120 dB
Surge Capability Test Method	ANSI/SCTE 81   Category A3 (6 kV, 200 A, Ring wave)
Surge Capability Waveform	100 KHz ring wave waveform

## General Specifications

Device Type	Splitter
Mounting	Horizontal
Video Ports, quantity	4
Brand	HomeConnect®
Application	Indoor   Outdoor
Warranty	Five years

## Mechanical Specifications

Material Type	Zinc
---------------	------

## Packed Dimensions

Carton Quantity	300
Height	203.20 mm   8.00 in
Length	520.70 mm   20.50 in
Width	330.20 mm   13.00 in

SV4G

Shipping Weight

20.41 kg | 45.00 lb

## Regulatory Compliance/Certifications

---

**Agency**

ISO 9001:2008

**Classification**

Designed, manufactured and/or distributed under this quality management system